


Dreibacken-Drehfutter

Three-jaw lathe chucks



Zylindrische Aufnahme nach DIN 6350, geteilte Backen

Centre mount according to DIN 6350, two-piece jaws


Guss / Cast iron

A (Ø) mm	B1 mm	C mm	D mm	E mm	F mm	G mm	K mm	L mm	RPM _{MAX} min ⁻¹	kg	Art.-Nr. / Order no.
125	60,8	4	95	32	108	3xM8	56	40	3200	5	ZE-6363-125
160	69,3	4	125	42	140	6xM10	67	43	3000	10	ZE-6363-160
200	79,8	4	160	55	176	6xM10	80	45	2500	17,5	ZE-6363-200
250	88,8	5	200	76	224	6xM12	95	53	2000	29	ZE-6363-250
315	99,1	5	260	103	286	6xM16	110	57	1500	50	ZE-6363-315
400	113,8	5	330	136	362	6xM16	127	67	1000	85	ZE-6363-400
500	130,8	5	420	190	458	6xM16	127	79	700	145	ZE-6363-500
630	146,3	7	545	252	586	6xM16	127	87	500	250	ZE-6363-630
800	170,3	20	450	320	368,3	-	127	87	300	402	ZE-6363-800

Stahl / Steel

125	66,3	4	95	35,5	108	3xM8	56	40	4800	5	ZE-8363-125
160	72,8	4	125	42	140	6xM10	67	43	4500	10	ZE-8363-160
200	82,8	4	160	55	176	6xM10	80	45	4000	17,5	ZE-8363-200
250	92,8	5	200	76	224	6xM12	95	53	3500	29	ZE-8363-250
315	101,3	5	260	103	286	6xM16	110	57	2800	50	ZE-8363-315
400	116,8	5	330	136	362	6xM16	127	67	2000	85	ZE-8363-400
500	129,8	5	420	190	458	6xM16	127	79	1200	145	ZE-8363-500
630	140,3	7	545	252	586	6xM16	127	87	1000	250	ZE-8363-630
800	161,3	20	450	320	368,3	-	127	87	450	402	ZE-8363-800

Inkl. je 1 Satz gehärteter Grund- und Umkehraufsatzbacken, Spannschlüssel, Befestigungsschrauben
 Incl. 1 set each of hardened base jaws and reversible top jaws, wrench, fixing screws



Kurzkegelaufnahme nach DIN 55026, einteilige Backen

According to DIN 55026, one-piece jaws

Stahl / Steel

Ø mm	KK Taper	Typ / Type	B mm	D mm	E mm	F mm	F1 mm	G mm	G1 mm	RPM _{MAX} min ⁻¹	kg	Art.-Nr. / Order no.
160	5	A1	68	82,6	42	-	62	-	M10	4500	10	ZE-8356-165
200	5	A1	78	82,6	42	-	62	-	M10	4000	19	ZE-8356-205
200	6	A1	78	106,4	55	-	82	-	M12	4000	19	ZE-8356-206
250	5	A2	89	82,6	76	104	-	M10	-	3500	32	ZE-8356-255
250	6	A1	89	106,4	55	-	82	-	M12	3500	32	ZE-8356-256
250	8	A1	89	139,7	76	-	111	-	M16	3500	32	ZE-8356-258
315	6	A2	96,2	106,4	103	133	-	M12	-	2800	55	ZE-8356-316
315	8	A1	96,2	139,7	80	-	111	-	M16	2800	55	ZE-8356-318
400	8	A2	108	139,7	136	171	-	M16	-	2000	92	ZE-8356-408
400	11	A1	108	196,9	130	-	165	-	M20	2000	92	ZE-8356-411
500	8	A2	119	139,7	136	171	-	M16	-	1200	160	ZE-8356-508
500	11	A2	119	196,9	190	235	-	M20	-	1200	160	ZE-8356-511
630	11	A2	129	196,9	190	235	-	M20	-	1000	285	ZE-8356-611
630	15	A2	129	285,8	252	330	-	M24	-	1000	285	ZE-8356-615

Inkl. je 1 Satz Dreh- und Bohrbacken, Spannschlüssel, Befestigungsschrauben
 Incl. 1 set each of solid jaws internally / externally stepped, wrench, fixing bolts