


Vierbacken-Drehfutter

Four-jaw lathe chucks




Kurzkegelaufnahme nach DIN 55027, einteilige Backen

According to DIN 55027, one-piece jaws

Stahl / Steel

Ø mm	KK Taper	B mm	D mm	E mm	F mm	RPM _{MAX} min ⁻¹	kg	Art.-Nr. / Order no.
125	3	59,5	54	35,5	75	4800	5	● ZE-8457-123
125	4	59,5	63,5	35,5	85	4800	5	● ZE-8457-124
160	4	68	63,5	42	85	4500	9	● ZE-8457-164
160	5	68	82,6	42	104,8	4500	9	● ZE-8457-165
200	4	78	63,5	55	85	4000	19	● ZE-8457-204
200	5	78	82,6	55	104,8	4000	19	● ZE-8457-205
200	6	78	106,4	55	133,4	4000	19	● ZE-8457-206
250	6	89	106,4	76	133,4	3500	32	● ZE-8457-256
250	8	89	139,7	76	171,4	3500	32	● ZE-8457-258
315	6	96,2	106,4	103	133,4	2800	51	● ZE-8457-316
315	8	96,2	139,7	103	171,4	2800	51	● ZE-8457-318
315	11	96,2	196,9	103	171,4	2800	51	● ZE-8457-311
400	8	108	139,7	136	171,4	2000	101	● ZE-8457-408
400	11	108	196,9	136	235	2000	101	● ZE-8457-411
500	8	119	139,7	136	171,4	1200	150	○ ZE-8457-508
500	11	119	196,9	190	235	1200	150	○ ZE-8457-511
630	11	129	196,9	190	235	1000	274	○ ZE-8457-611
630	15	129	285,5	252	330,2	1000	274	○ ZE-8457-615

Inkl. je 1 Satz Dreh- und Bohrbacken, Spannschlüssel, Befestigungsbolzen
 Incl. 1 set each of solid jaws internally / externally stepped, wrench, fixing screws



Kurzkegelaufn. nach DIN 55029 (Camlock), einteilige Backen

According to DIN 55029 (Camlock), one-piece jaws

Stahl / Steel

Ø mm	KK Taper	B mm	D mm	E mm	F mm	RPM _{MAX} min ⁻¹	kg	Art.-Nr. / Order no.
125	3	59,5	54	35,5	70,6	4800	5	● ZE-8459-123
125	4	59,5	63,5	35,5	82,6	4800	5	● ZE-8459-124
160	4	68	63,5	42	82,6	4500	9	● ZE-8459-164
160	5	68	82,6	42	104,8	4500	9	● ZE-8459-165
200	4	78	63,5	55	82,6	4000	19	● ZE-8459-204
200	5	78	82,6	55	104,8	4000	19	● ZE-8459-205
200	6	78	106,4	55	133,4	4000	19	● ZE-8459-206
250	6	89	106,4	76	133,4	3500	32	● ZE-8459-256
250	8	89	139,7	76	171,4	3500	32	● ZE-8459-258
315	6	96,2	106,4	103	133,4	2800	51	● ZE-8459-316
315	8	96,2	139,7	103	171,4	2800	51	● ZE-8459-318
400	8	108	139,7	136	171,4	2000	101	● ZE-8459-408
400	11	108	196,9	136	235	2000	101	● ZE-8459-411
500	8	119	139,7	136	171,4	1200	150	○ ZE-8459-508
500	11	119	196,9	190	235	1200	150	○ ZE-8459-511
630	11	129	196,9	190	235	1000	274	○ ZE-8459-611
630	15	129	285,5	252	330,2	1000	274	○ ZE-8459-615

Inkl. je 1 Satz Dreh- und Bohrbacken, Spannschlüssel, Befestigungsbolzen
 Incl. 1 set each of solid jaws internally / externally stepped, wrench, fixing screws